



DURABLE ACOUSTICAL COMFORT



DURABLE, ACOUSTICAL, AND COMFORTABLE UNDERLAYMENT

NO.2024-07

DURALUX™

WE'VE BEEN REVOLUTIONIZING FLOOR ACOUSTICS SINCE 1957

DURALUX

RESIDENTIAL USE

Dura has a clear goal: produce the highest performing underlay and carpet cushion products while contributing to the preservation of our environment for generations to come. Through our unique process of giving a second life to used rubber, we've achieved our lofty goal by creating products that absorb sound like no other and lasts for years.

Our Duralux underlayment places an emphasis on underfoot comfort. Its advanced design delivers exceptional sound absorption and reduces noise transfer, creating a peaceful environment for guests and residents. Having superior durability, Duralux withstands heavy foot traffic while extending the life of your carpet. Ideal for high-end area rugs and stair runners in luxurious hotels, condos, and private homes.

HIGH-PERFORMANCE UNDERLAYMENT



ENGINEERED
HARDWOOD
AND LAMINATE



CERAMIC



VINYL



CARPET



✓ **SUITABLE FOR MODERATE-
TO-HEAVY FOOT TRAFFIC**

✓ **MADE FROM RECYCLED RUBBER**


✓ **IDEAL FOR HIGH-END AREA RUGS
AND STAIR RUNNERS**

✓ **RETAINS ITS SOUNDPROOFING
QUALITIES**

✓ **LASTS A LIFETIME**

WHAT MAKES DURALUX THE NEW STANDARD

**GREATLY REDUCES
IMPACT SOUND**



**PROVIDES UNDERFOOT
COMFORT & DOES NOT
COLLAPSE OVER TIME**



ENSURES A LUXURIOUS FEEL



**GUARANTEED TO WORK OVER
RADIANT HEATED FLOORS**



**RESISTS MOLD, MILDEW,
AND FUNGUS GROWTH**



EASY TO INSTALL



**CONTRIBUTES TO
LEED CREDITS**



**GREEN LABEL
PLUS+ CERTIFIED**




**MADE FROM
RECYCLED RUBBER**



ACOUSTICAL TESTING

PERFORMED BY:
INTERTEK


ASTM E90 + ASTM E492



Carpet	IIC*85
Duralux 7 mm (9/32")	
6" Concrete Slab	IIC*40
Wire Hung Ceiling Grid	

Approved and tested by experts

Duralux 7 mm (9/32") was tested under a 12 mm carpet and over a 152 mm concrete slab, obtaining an IIC 85. IIC is a measure of impact sound transmission from one floor to another. The higher the IIC rating, the better quality of sound absorption.



Duralux Specifications

The sound rated floor material shall be an open cellular rubber shall be an open cellular rubber reinforced with solid rubber particles bonded to jute or fiberglass backing, 7 mm (9/32") thick, approximately 74 oz/yd² in weight and 22 lb/ft³ in density. The product shall have an IIC rating of 85 (tested as per ASTM E90 + ASTM E492) based on the construction detailed in this brochure. The acoustical material shall be Duralux 7 mm (9/32") manufactured by: Dura Undercushions Ltd.

We invite you to contact us for any inquiries via email: info@duraundercushions.com or via phone: **1-800-295-4126**

IMPERIAL MATERIAL SPECIFICATIONS

Thickness	0.27 in
"R" Value	0.58
Mass	74 oz / sq.yd
Density	22 lb / cu. ft
Tensile	22.8 lb / in
Content	Minimum 95% recycled rubber
Roll Size	15 sq. yd
Roll Weight	69 lb
Roll Width	54 in.
Roll Length	30 ft.
Roll Diameter	11 in.
Coverage	135 sq. ft
Acoustic Value	IIC 85 / ASTM E90 and ASTM E492 - Impact Sound Transmission (With a carpet)
Green Quality	CRI Green Label Plus approved
Anti-Microbial	Naturally resists mold, mildew and fungus growth
Radiant Heated Floors	Suitable for radiant heated floor
LEED	Contributes up to 6 credits
Flammability	PASS Pill Test / ASTM D2859 / Class 1 / ASTM E 648 - Radiant Panel Test / As an assembly with a Class 1 commercial carpet
Warranty	Lifetime*

METRIC MATERIAL SPECIFICATIONS

Thickness	6.86 mm
"R" Value	0.58
Mass	2.51 kg / sq. m
Density	352.4 kg / cu. m
Tensile	200 N / 5 cm
Content	Minimum 95% recycled rubber
Roll Size	12.54 sq. m
Roll Weight	31.3 kg
Roll Width	1.37 m
Roll Length	9.14 m
Roll Diameter	27.94 cm
Coverage	12.54 sq. m
Acoustic Value	IIC 85 / ASTM E90 and ASTM E492 - Impact Sound Transmission (With a carpet)
Green Quality	CRI Green Label Plus approved
Anti-Microbial	Naturally resists mold, mildew and fungus growth
Radiant Heated Floors	Suitable for radiant heated floor
LEED	Contributes up to 6 credits
Flammability	PASS Pill Test / ASTM D2859 / Class 1 / ASTM E 648 - Radiant Panel Test / As an assembly with a Class 1 commercial carpet
Warranty	Lifetime*

QUICK AND EASY TO INSTALL

TACKLESS AND STRETCH-IN INSTALLATION PROCEDURE

1
Measure the length and width of the room and cut DURALUX to size, leaving a 1/2" gap around the perimeter of the room.

2
DURALUX should be laid black side down. Ensure that it covers the entire area of the room.

3
Use double-sided carpet tape to secure the edges of DURALUX to the floor along the perimeter of the room, leaving a 1/2" gap around the edges.

4
Install tack strips around the perimeter of the room, making sure to leave a 1/4" gap between the strip and the wall.

5
Stretch the carpet over DURALUX and tuck the carpet into the gap between the tack strip and the wall using a knee kicker or power stretcher.

6
Use a carpet knife to trim any excess carpet along the edges of the room.



Caution:

Using poor quality adhesive, incorrect type, or improper application method can cause installation issues. Please contact Dura Undercushions for the installation of DURALUX using the double-glue procedure.

When following the double glue-installation procedure, consider using a 1/8" x 1/8" x 1/8" U-notch trowel for even adhesive coverage.

WARRANTY

Dura underlayments are warranted to retain their essential firmness, resilience, and porosity through the useful life of the floor covering under which they are installed. This warranty applies to all types of indoor installations. In the event of a confirmed product failure due to defective manufacture the company will replace, without charge, the defective portion of the underlayment with new equivalent product.

This warranty is valid only when the product is used in accordance with our instructions and for its intended purpose and does not cover defects or failures due to inappropriate use or abuse.



Find us in
MasterSpec[®]
Powered by Deltek Specpoint[®]



DISCOVER MORE

DURABLE ACOUSTICAL COMFORT



For Engineered Hardwood and Laminated Flooring

YOU NEED:
DURA-SON
DURA-SON MB

MULTI-RESILIENT LAYER FLOORING

YOU NEED:
DURACOUSTIC



For Carpets

YOU NEED:
DURACUSHION
SUPERDURA
PROTECTOR
DURALUX

MULTI-RESILIENT LAYER FLOORING

YOU NEED:
DURACOUSTIC

The durability of our products are the solution to all your acoustical needs. They will outlast and maintain their acoustical and comfort qualities throughout their lifetime.



For Ceramics

YOU NEED:
DURAQUIET

MULTI-RESILIENT LAYER FLOORING

YOU NEED:
DURACOUSTIC



For Vinyl

YOU NEED:
DURAQUIET

MULTI-RESILIENT LAYER FLOORING

YOU NEED:
DURACOUSTIC



DURABLE ACOUSTICAL COMFORT

**8525 CHEMIN DELMEADE, MONTREAL
QC H4T 1M1**

1-800-295-4126

INFO@DURAUNDERCUSHIONS.COM

WWW.DURACUSHION.COM

