



DURABLE ACOUSTICAL COMFORT



DURABLE, ACOUSTICAL, AND COMFORTABLE UNDERLAYMENT

NO.2025-01

DURALUX™ GRIP 3MM

NON-SLIP RUG PAD

IMPERIAL MATERIAL SPECIFICATIONS

Thickness	0.137 in
Mass	34 oz / sq.yd
Density	22 lb / cu. ft
Tensile	22.8 lb / in
Content	Minimum 95% recycled rubber
Roll Size	24 sq. yd
Roll Weight	55 lb
Roll Width	54 in.
Roll Length	48 ft.
Roll Diameter	10 in.
Coverage	216 sq. ft
Acoustic Value	IIC 70 / ASTM E90 and ASTM E492 - Impact Sound Transmission (Preliminary rating based on DuraPad 2mm. Final results pending ongoing product testing.)
Green Quality	CRI Green Label Plus approved
Anti-Microbial	Naturally resists mold, mildew and fungus growth
Radiant Heated Floors	Compatible
LEED	Contributes up to 4 credits
Warranty	Lifetime*

METRIC MATERIAL SPECIFICATIONS

Thickness	3 mm
Mass	1.24 kg / sq. m
Density	352.4 kg / cu. m
Tensile	200 N / 5 cm
Content	Minimum 95% recycled rubber
Roll Size	20.06 sq. m
Roll Weight	25 kg
Roll Width	1.37 m
Roll Length	14.63 m
Roll Diameter	25.4 cm
Coverage	20 sq. m
Acoustic Value	IIC 70 / ASTM E90 and ASTM E492 - Impact Sound Transmission (Preliminary rating based on DuraPad 2mm. Final results pending ongoing product testing.)
Green Quality	CRI Green Label Plus approved
Anti-Microbial	Naturally resists mold, mildew and fungus growth
Radiant Heated Floors	Compatible
LEED	Contributes up to 4 credits
Warranty	Lifetime*

ACOUSTICAL TESTING

ONGOING PRODUCT TESTING

NOTE:

Duralux Grip 3mm (1/8") is projected to achieve an IIC rating of 70 based on preliminary testing and comparative data from DuraPad 2mm. IIC is a measure of impact sound transmission from one floor to another. The higher the IIC rating, the better quality of sound absorption.

Duralux Grip 3mm (1/8") is not intended for acoustic insulation. While product-specific acoustic testing is currently in progress, this underlayment is engineered primarily for enhanced rug stability, foot traction, and low-profile transitions in high-traffic areas.

DURALUX SELECTION GUIDE

	DURALUX GRIP 3MM	DURALUX COMFORT 7MM
PRIMARY FUNCTION	Stability, Traction, Low-Profile	Comfort, Carpet Longevity, Sound Absorption
IDEAL USE AREAS	Entryways, Hallways, Door Zones	Living Rooms, Master Bedrooms, Hotel Lobbies
THICKNESS	3 mm	7 mm
ACOUSTIC RATING	IIC 70	IIC 85

DISCOVER MORE

DURABLE ACOUSTICAL COMFORT



For Engineered Hardwood and Laminated Flooring

YOU NEED:
DURA-SON
DURA-SON MB

MULTI-RESILIENT LAYER FLOORING

YOU NEED:
DURACOUSTIC



For Carpets

YOU NEED:
DURACUSHION
SUPERDURA
PROTECTOR
DURALUX

MULTI-RESILIENT LAYER FLOORING

YOU NEED:
DURACOUSTIC

The durability of our products are the solution to all your acoustical needs. They will outlast and maintain their acoustical and comfort qualities throughout their lifetime.



For Ceramics

YOU NEED:
DURAQUIET

MULTI-RESILIENT LAYER FLOORING

YOU NEED:
DURACOUSTIC



For Vinyl

YOU NEED:
DURAQUIET

MULTI-RESILIENT LAYER FLOORING

YOU NEED:
DURACOUSTIC



DURABLE ACOUSTICAL COMFORT

**8525 CHEMIN DELMEADE, MONTREAL
QC H4T 1M1**

1-800-295-4126

INFO@DURAUNDERCUSHIONS.COM

WWW.DURACUSHION.COM

