



DURABLE ACOUSTICAL COMFORT



DURABLE, ACOUSTICAL, AND COMFORTABLE UNDERLAYMENT

NO.2025-01

DURALUX™ GRIP 3MM

NON-SLIP RUG PAD

WE'VE BEEN REVOLUTIONIZING FLOOR ACOUSTICS SINCE 1957

DURALUX GRIP 3MM

RESIDENTIAL & COMMERCIAL USE

Dura has a clear goal: produce the highest performing underlay and carpet cushion products while contributing to the preservation of our environment for generations to come. Through our unique process of giving a second life to used rubber, we've achieved our lofty goal by creating products that absorb sound like no other and lasts for years.

Designed for high-traffic areas where traction and stability are essential, Duralux Grip 3mm is a non-slip rug pad ideal for area rugs and runners in tight clearance zones. With a refined 3mm thickness, it seamlessly fits under rugs in entryways, hallways, and near door thresholds—where low profile is key and rugs must stay firmly in place. Its jute backing enhances grip and slip resistance, offering reliable support in busy residential and commercial settings.

HIGH-PERFORMANCE UNDERLAYMENT



ENGINEERED
HARDWOOD
AND LAMINATE



CERAMIC



VINYL



CARPET



✓ **BUILT TO PERFORM IN HEAVY-
FOOT-TRAFFIC SPACES**

✓ **ENGINEERED FOR GRIP AND
STABILITY**

✓ **FOR AREA RUGS AND CARPET
RUNNERS**

✓ **MADE FROM RECYCLED RUBBER**

✓ **RETAINS ITS SOUNDPROOFING
QUALITIES**

IMPERIAL MATERIAL SPECIFICATIONS

Thickness	0.137 in
Mass	34 oz / sq.yd
Density	22 lb / cu. ft
Tensile	22.8 lb / in
Content	Minimum 95% recycled rubber
Roll Size	24 sq. yd
Roll Weight	55 lb
Roll Width	54 in.
Roll Length	48 ft.
Roll Diameter	10 in.
Coverage	216 sq. ft
Acoustic Value	IIC 70 / ASTM E90 and ASTM E492 - Impact Sound Transmission (Preliminary rating based on DuraPad 2mm. Final results pending ongoing product testing.)
Green Quality	CRI Green Label Plus approved
Anti-Microbial	Naturally resists mold, mildew and fungus growth
Radiant Heated Floors	Compatible
LEED	Contributes up to 4 credits
Warranty	Lifetime*

METRIC MATERIAL SPECIFICATIONS

Thickness	3 mm
Mass	1.24 kg / sq. m
Density	352.4 kg / cu. m
Tensile	200 N / 5 cm
Content	Minimum 95% recycled rubber
Roll Size	20.06 sq. m
Roll Weight	25 kg
Roll Width	1.37 m
Roll Length	14.63 m
Roll Diameter	25.4 cm
Coverage	20 sq. m
Acoustic Value	IIC 70 / ASTM E90 and ASTM E492 - Impact Sound Transmission (Preliminary rating based on DuraPad 2mm. Final results pending ongoing product testing.)
Green Quality	CRI Green Label Plus approved
Anti-Microbial	Naturally resists mold, mildew and fungus growth
Radiant Heated Floors	Compatible
LEED	Contributes up to 4 credits
Warranty	Lifetime*

WHAT MAKES DURALUX GRIP 3MM THE NEW STANDARD

**GREATLY REDUCES
IMPACT SOUND**



**PROVIDES UNDERFOOT
COMFORT & DOES NOT
COLLAPSE OVER TIME**



**ENHANCES FOOT TRACTION
& RUG STABILITY**



**GUARANTEED TO WORK OVER
RADIANT HEATED FLOORS**



**RESISTS MOLD, MILDEW,
AND FUNGUS GROWTH**



EASY TO INSTALL



**CONTRIBUTES TO
LEED CREDITS**



**GREEN LABEL
PLUS+ CERTIFIED**



**MADE FROM
RECYCLED RUBBER**



ACOUSTICAL TESTING

ONGOING PRODUCT TESTING

NOTE:

Duralux Grip 3mm (1/8") is projected to achieve an IIC rating of 70 based on preliminary testing and comparative data from DuraPad 2mm. IIC is a measure of impact sound transmission from one floor to another. The higher the IIC rating, the better quality of sound absorption.

Duralux Grip 3mm (1/8") is not intended for acoustic insulation. While product-specific acoustic testing is currently in progress, this underlayment is engineered primarily for enhanced rug stability, foot traction, and low-profile transitions in high-traffic areas.

DURALUX SELECTION GUIDE

	DURALUX GRIP 3MM	DURALUX COMFORT 7MM
PRIMARY FUNCTION	Stability, Traction, Low-Profile	Comfort, Carpet Longevity, Sound Absorption
IDEAL USE AREAS	Entryways, Hallways, Door Zones	Living Rooms, Master Bedrooms, Hotel Lobbies
THICKNESS	3 mm	7 mm
ACOUSTIC RATING	IIC 70	IIC 85

QUICK AND EASY TO INSTALL

CUT & LAY INSTALLATION PROCEDURE

- ① **Unroll
DURALUX GRIP
on the floor.**
- ② **Trim DURALUX
GRIP with a
carpet knife
to be slightly
smaller than
the runner
(approximately
1/2" narrower
on each side).**
- ③ **Lay DURALUX
GRIP with the
jute side facing
up, rubber side
down (toward
the rug).**
- ④ **Place the
runner directly
on top of
DURALUX GRIP
and adjust as
needed.**



Caution:

Using poor quality adhesive, incorrect type, or improper application method can cause installation issues. Please contact Dura Undercushions for the installation of DURALUX using the double-glue procedure.

When following the double glue-installation procedure, consider using a 1/8" x 1/8" x 1/8" U-notch trowel for even adhesive coverage.

We invite you to contact us
for any inquiries via email:
info@duraundercushions.com
or via phone:
1-800-295-4126

WARRANTY

Dura underlayments are warranted to retain their essential firmness, resilience, and porosity through the useful life of the floor covering under which they are installed. This warranty applies to all types of indoor installations. In the event of a confirmed product failure due to defective manufacture the company will replace, without charge, the defective portion of the underlayment with new equivalent product.

This warranty is valid only when the product is used in accordance with our instructions and for its intended purpose and does not cover defects or failures due to inappropriate use or abuse.



DISCOVER MORE

DURABLE ACOUSTICAL COMFORT



For Engineered Hardwood and Laminated Flooring

YOU NEED:

DURA-SON
DURA-SON MB

MULTI-RESILIENT LAYER FLOORING

YOU NEED:

DURACOUSTIC



For Carpet & Carpet Tile

YOU NEED:

DURACUSHION (Carpet)
SUPERDURA (Carpet)
PROTECTOR (Carpet)
DURALUX (Carpet)

DURAPAD (Carpet Tile)
DURAQUIET (Carpet Tile)

MULTI-RESILIENT LAYER FLOORING

YOU NEED:

DURACOUSTIC

The durability of our products are the solution to all your acoustical needs. They will outlast and maintain their acoustical and comfort qualities throughout their lifetime.



For Ceramics

YOU NEED:
DURAQUIET

MULTI-RESILIENT LAYER FLOORING

YOU NEED:
DURACOUSTIC



For Vinyl

YOU NEED:
DURAPAD (LVT/LVP)
DURAQUIET (LVT/LVP/Sheet Vinyl)

MULTI-RESILIENT LAYER FLOORING

YOU NEED:
DURACOUSTIC



DURABLE ACOUSTICAL COMFORT

**8525 CHEMIN DELMEADE, MONTREAL
QC H4T 1M1**

1-800-295-4126

INFO@DURAUNDERCUSHIONS.COM

WWW.DURACUSHION.COM

