



SUSTAINABLE ACOUSTICAL COMFORT



---

SUSTAINABLE, ACOUSTICAL, AND COMFORTABLE UNDERLAYMENT NO.2026

---

# DURALUX™ GRIP 3MM

NON-SLIP RUG PAD

---

# IMPERIAL MATERIAL SPECIFICATIONS

---

<b>Thickness</b>	0.137 in
<b>Mass</b>	34 oz / sq.yd
<b>Density</b>	22 lb / cu. ft
<b>Tensile</b>	22.8 lb / in
<b>Content</b>	Minimum 95% recycled rubber
<b>Roll Size</b>	24 sq. yd
<b>Roll Weight</b>	55 lb
<b>Roll Width</b>	54 in.
<b>Roll Length</b>	48 ft.
<b>Roll Diameter</b>	10 in.
<b>Coverage</b>	216 sq. ft
<b>Acoustic Value</b>	IIC 70 / ASTM E90 and ASTM E492 - Impact Sound Transmission (Preliminary rating based on DuraPad 2mm. Final results pending ongoing product testing.)
<b>Green Quality</b>	CRI Green Label Plus approved
<b>Anti-Microbial</b>	Naturally resists mold, mildew and fungus growth
<b>Radiant Heated Floors</b>	Compatible
<b>LEED</b>	Contributes up to 4 credits
<b>Warranty</b>	Lifetime*

---

---

# METRIC MATERIAL SPECIFICATIONS

<b>Thickness</b>	3 mm
<b>Mass</b>	1.24 kg / sq. m
<b>Density</b>	352.4 kg / cu. m
<b>Tensile</b>	200 N / 5 cm
<b>Content</b>	Minimum 95% recycled rubber
<b>Roll Size</b>	20.06 sq. m
<b>Roll Weight</b>	25 kg
<b>Roll Width</b>	1.37 m
<b>Roll Length</b>	14.63 m
<b>Roll Diameter</b>	25.4 cm
<b>Coverage</b>	20 sq. m
<b>Acoustic Value</b>	IIC 70 / ASTM E90 and ASTM E492 - Impact Sound Transmission (Preliminary rating based on DuraPad 2mm. Final results pending ongoing product testing.)
<b>Green Quality</b>	CRI Green Label Plus approved
<b>Anti-Microbial</b>	Naturally resists mold, mildew and fungus growth
<b>Radiant Heated Floors</b>	Compatible
<b>LEED</b>	Contributes up to 4 credits
<b>Warranty</b>	Lifetime*

---

# ACOUSTICAL TESTING

## ONGOING PRODUCT TESTING

**NOTE:**

Duralux Grip 3mm (1/8") is projected to achieve an IIC rating of 70 based on preliminary testing and comparative data from DuraPad 2mm. IIC is a measure of impact sound transmission from one floor to another. The higher the IIC rating, the better quality of sound absorption.

Duralux Grip 3mm (1/8") is not intended for acoustic insulation. While product-specific acoustic testing is currently in progress, this underlayment is engineered primarily for enhanced rug stability, foot traction, and low-profile transitions in high-traffic areas.

---

## DURALUX SELECTION GUIDE

	<b>DURALUX GRIP 3MM</b>	<b>DURALUX COMFORT 7MM</b>
<b>PRIMARY FUNCTION</b>	Stability, Traction, Low-Profile	Comfort, Carpet Longevity, Sound Absorption
<b>IDEAL USE AREAS</b>	Entryways, Hallways, Door Zones	Living Rooms, Master Bedrooms, Hotel Lobbies
<b>THICKNESS</b>	3 mm	7 mm
<b>ACOUSTIC RATING</b>	IIC 70	IIC 85

# DISCOVER MORE

## DURABLE ACOUSTICAL COMFORT



### For Engineered Hardwood and Laminated Flooring

**YOU NEED:**  
DURA-SON  
DURA-SON MB

### MULTI-RESILIENT LAYER FLOORING

**YOU NEED:**  
DURACOUSTIC



### For Carpet & Carpet Tile

**YOU NEED:**  
DURACUSHION (Carpet)  
SUPERDURA (Carpet)  
PROTECTOR (Carpet)  
DURALUX (Carpet)

DURAPAD (Carpet Tile)  
DURAQUIET (Carpet Tile)

### MULTI-RESILIENT LAYER FLOORING

**YOU NEED:**  
DURACOUSTIC

The durability of our products are the solution to all your acoustical needs. They will outlast and maintain their acoustical and comfort qualities throughout their lifetime.



---

### For Ceramics

**YOU NEED:**  
DURAQUIET

---

### MULTI-RESILIENT LAYER FLOORING

**YOU NEED:**  
DURACOUSTIC



---

### For Vinyl

**YOU NEED:**  
DURAPAD (LVT/LVP)  
DURAQUIET (LVT/LVP/Sheet Vinyl)

---

### MULTI-RESILIENT LAYER FLOORING

**YOU NEED:**  
DURACOUSTIC



SUSTAINABLE ACOUSTICAL COMFORT

---

**8525 CHEMIN DELMEADE, MONTREAL  
QC H4T 1M1**

---

**1-800-295-4126**

---

**INFO@DURAUNDERCUSHIONS.COM**

---

**[WWW.DURACUSHION.COM](http://WWW.DURACUSHION.COM)**

