



SUSTAINABLE ACOUSTICAL COMFORT



---

SUSTAINABLE, ACOUSTICAL, AND COMFORTABLE UNDERLAYMENT NO.2026

---

**DURAQUIET™**

UP TO IIC 74

---

# IMPERIAL MATERIAL SPECIFICATIONS

---

<b>Thickness</b>	0.125 in
<b>“R” Value</b>	0.2
<b>Mass</b>	66 oz / sq.yd
<b>Density</b>	46 lb / cu. ft
<b>Content</b>	Minimum 95% recycled rubber
<b>Roll Size</b>	16.67 sq. yd
<b>Roll Weight</b>	69 lb
<b>Roll Width</b>	60 in.
<b>Roll Length</b>	30 ft.
<b>Roll Diameter</b>	8 in.
<b>Coverage</b>	150 sq. ft
<b>Acoustic Value</b>	IIC 74 / ASTM E492 and E90 - Impact Insulating Class
<b>Green Quality</b>	CRI Green Label Plus approved
<b>Anti-Microbial</b>	Naturally resists mold, mildew and fungus growth
<b>Radiant Heated Floors</b>	Compatible
<b>LEED</b>	Contributes up to 6 credits
<b>Flammability</b>	PASS Pill Test / ASTM D2859 / Class 1 / ASTM E 648 - Radiant Panel Test / As an assembly with a Class 1 commercial carpet
<b>Warranty</b>	Lifetime*

---

---

# METRIC MATERIAL SPECIFICATIONS

---


<b>Thickness</b>	3 mm
<b>“R” Value</b>	0.2
<b>Mass</b>	2.24 kg / sq. m
<b>Density</b>	736.84 kg / cu. m
<b>Content</b>	Minimum 95% recycled rubber
<b>Roll Size</b>	13.94 sq. m
<b>Roll Weight</b>	31.3 kg
<b>Roll Width</b>	1.52 m
<b>Roll Length</b>	9.14 m
<b>Roll Diameter</b>	20.32 cm
<b>Coverage</b>	13.94 sq. m
<b>Acoustic Value</b>	IIC 74 / ASTM E492 and E90 - Impact Insulating Class
<b>Green Quality</b>	CRI Green Label Plus approved
<b>Anti-Microbial</b>	Naturally resists mold, mildew and fungus growth
<b>Radiant Heated Floors</b>	Compatible
<b>LEED</b>	Contributes up to 6 credits
<b>Flammability</b>	PASS Pill Test / ASTM D2859 / Class 1 / ASTM E 648 - Radiant Panel Test / As an assembly with a Class 1 commercial carpet
<b>Warranty</b>	Lifetime*

---

# ACOUSTICAL TESTING

**PERFORMED BY:**  
**INTERTEK**

## ASTM E90 + ASTM E492



Luxury Vinyl Tile  
Duraquiet 3 mm (1/8")  
Plywood (2 x 3/8")  
Super Dura 10 mm (25/64")  
6" Concrete Slab  
Suspended Ceiling

IIC\*74

Vinyl  
Duraquiet 3 mm (1/8")  
Cement board (2 x 1/2")  
Duracoustic 8 mm (5/16")

IIC\*71

Vinyl  
Duraquiet 3 mm (1/8")

IIC\*66

Ceramic Tile  
Duraquiet 3 mm (1/8")

IIC\*63

6" Concrete Slab  
Wire Hung Ceiling Grid


IIC\*40

## Approved and tested by experts

Duraquiet 3 mm (1/8") was tested under a luxury vinyl tile floor and over a 6" concrete slab. Duraquiet 3mm (1/8") obtained an IIC 74. IIC is a measure of impact sound transmission from one floor to another. The higher the IIC rating, the better quality of sound absorption.

## Duraquiet Specifications

The sound rated floor material shall be a closed cellular rubber reinforced with solid rubber particles, 3 mm (1/8") thick, approximately 66 oz/yd<sup>2</sup> in weight and 46 lb/ft<sup>3</sup> in density. The product shall have an IIC rating of 74 (tested as per ASTM E90 + ASTM E492) based on the construction detailed in this brochure. The acoustical material shall be Duraquiet 3 mm (1/8") manufactured by : Dura Undercushions Ltd.



We invite you to contact us for any inquiries via email: [info@duraundercushions.com](mailto:info@duraundercushions.com) or via phone: **1-800-295-4126**

# DISCOVER MORE

## DURABLE ACOUSTICAL COMFORT



### For Engineered Hardwood and Laminated Flooring

**YOU NEED:**  
DURA-SON  
DURA-SON MB

### MULTI-RESILIENT LAYER FLOORING

**YOU NEED:**  
DURACOUSTIC



### For Carpet & Carpet Tile

**YOU NEED:**  
DURACUSHION (Carpet)  
SUPERDURA (Carpet)  
PROTECTOR (Carpet)  
DURALUX (Carpet)

DURAPAD (Carpet Tile)  
DURAQUIET (Carpet Tile)

### MULTI-RESILIENT LAYER FLOORING

**YOU NEED:**  
DURACOUSTIC

The durability of our products are the solution to all your acoustical needs. They will outlast and maintain their acoustical and comfort qualities throughout their lifetime.



---

### For Ceramics

**YOU NEED:**  
DURAQUIET

---

### MULTI-RESILIENT LAYER FLOORING

**YOU NEED:**  
DURACOUSTIC



---

### For Vinyl

**YOU NEED:**  
DURAPAD (LVT/LVP)  
DURAQUIET (LVT/LVP/Sheet Vinyl)

---

### MULTI-RESILIENT LAYER FLOORING

**YOU NEED:**  
DURACOUSTIC



SUSTAINABLE ACOUSTICAL COMFORT

---

**8525 CHEMIN DELMEADE, MONTREAL  
QC H4T 1M1**

---

**1-800-295-4126**

---

**INFO@DURAUNDERCUSHIONS.COM**

---

**[WWW.DURACUSHION.COM](http://WWW.DURACUSHION.COM)**

